ZORG
North America LLC

High Definition Digital Commercial Wireless Monitor and Camera System

Part# 3210

Features of 3210

- 7" LCD color monitor with HD 1280 x 720P high resolution display
- Expandable 4/2/1 channel camera input
- Wireless range of up to 200m transmission distance (line of sight)
- Blade and Standard Antennas Included for installation ease (5Db)
- Night-vision Assist With 10 High Intensity LED Emitters
- 7" monitor with built-in DVR
- SD card data storage (Card Not Incld.)
- Quad, split or single screen display
- Mirror and normal image switch
- Selectable parking guidelines - ON/OFF
- Backlit Control Keys
- Wide voltage input: DC 12V – 24V
- Removable Sun Shade Included
- Vibration: 10G
- Three year warranty

* Includes 1 piece 3211 Camera in Kit.

Specifications for 3210

Screen Size	7.0" LCD monitor
Transmission Frequency	2.4G (digital)
Transmission Resolution	High definition 1920*1080
Transmission Delay (Ave)	150mS
RF Pairing	Auto
Auto Frequency Hopping	125 CH (overlapping hopping channel to avoid noise)
Voltage	DC12 ~ 24V
Consumption	< 3W
Brightness	500cdm
Mirror Image	Yes (via menu select)
Speaker	Yes
Auto Brightness / Dimming	Yes
Camera Selection	1-4 (auto or manual)
Dimensions On Bracket	8"W x 5.5"H x 1.25"D
Weight	1lb 3oz
Temperature	-20°C to +70°C

Note: Use only Class 10 or above SD memory cards (Max 128 GB) for reliable recording and performance.

ZORG
North America LLC

High Definition Digital Commercial Camera

Part #3211

Features of 3211

- HD1920*1080 high resolution
- Wireless range of up to 200m transmission distance (line of sight)
- Automatic pairing function of monitor & camera(s)
- Night-vision Assist With 10 High Intensity LED Emitters
- Built-in microphone
- Wide voltage input: 12V ~ 24V system
- Vibration: 10G
- Housing: aluminium-alloy w/ anti-UV surface painting
- Angle adjustable
- Three year warranty

Specifications for 3211

Image (Main Chip)	1/3" CMOS BSI color 1280H x 960V pixels
Voltage	DC12 ~ 24V
Consumption	< 1W
Lens Angle	130º diagonal
Microphone	Yes
IR LED Control	Photo sensor automatic control
Infrared LEDs	10 (10m visibility)
Housing	Aluminium alloy
Mechanical Vibration	10G
Mounting	Permanent tilt bracket
Dimensions On Bracket	3.5"W x 3.25"H x 3"D mm
Weight	12.1oz
Temperature	-20°C to +70°C
IP rating (Water Resistance)	IP69K